

DATA SHEET

119

BRICK, MASONRY AND CONCRETE COLOUR STAINER

(Page 1 of 3)

V1-28/11/2014

DESCRIPTION

- 119 is a water based penetrating stainer, designed for easy and safe application, to give natural colour effects to cement based surfaces.
-

PROPERTIES

- Penetrates most cement surfaces including damp concrete
 - Easy to apply
 - No solvents, clean equipment with water
 - Good UV resistance
-

RECOMMENDED AREAS FOR USE

- Counter tops
 - Ablution blocks
 - Schools and hospitals
 - Kitchens
 - Passages and walkways
-

SURFACE PREPARATION

- All surfaces to be clean and sound free of dust, oil and grease. New concrete should be acid etched to remove surface laitance.
-

DATA SHEET

119

BRICK, MASONRY AND CONCRETE COLOUR STAINER

(Page 2 of 3)

V1-28/11/2014

APPLICATION

- Apply by sponge, brush or roller to achieve the desired effect.
-

SEALING

- Depending on the final finish required a suitable sealer and wear resistant top- coat should be applied. (Contact a technical representative for specialist advice)
-

CLEANING EQUIPMENT

- Clean all equipment immediately after use with water.
-

TOXICITY

- 119 is a relatively non-toxic and safe to use water based stain. Refer to the relevant 16 point Material Safety Data Sheet.
-

HOW TO SPECIFY

- All surfaces to be suitably prepared and coated with 119 Water Based Stainer, applied according to the manufacturer's instructions.
-

DATA SHEET

119

BRICK, MASONRY AND CONCRETE COLOUR STAINER

(Page 3 of 3)

VI-28/11/2014

TECHNICAL DATA

TYPE	: Urethane Acrylic
NUMBER OF COMPONENTS	: 1
COLOURS	: See Colour Chart
VOC	: 5.2
FINISH	: Satin
NUMBER OF COATS	: 1 or 3 coats
OVERCOATING TIME	: 2hrs – 4hrs
TOUCH DRY	: 2hrs
SOLIDS (By Volume)	: 40%
AVERAGE SPREAD RATE	: 10m ² /l/coat
APPLICATION TEMPERATURE	: 5 to 40°C
SHELF LIFE	: 12 Months
PACKAGING	: 5 and 20 litres

The technical data furnished is obtained from controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven fault our liability will be limited to the replacement of the product only. It is the users' responsibility to confirm the currency of product data sheets.