

DATA SHEET

407
BONDING PRIMER (PREVIOUSLY "P1" PRIMER)

(Page 1 of 3)

V1-28/11/2014

DESCRIPTION

- 407 is a solvent based single pack penetrating and bonding primer with excellent alkali resistance, based on an Acrylic Resin

RECOMMENDED AREAS FOR USE

- As a bonding primer for masonry, fibre cement, asphalt and most other surfaces prior to applying Liquid Plastic Waterproof coatings.

SURFACE PREPARATION

- All surfaces must be clean, dry and mechanically sound, free of oil, dirt and dust.
- New concrete and cement screeds must be abraded or acid etched to remove surface laitance.

CLEANING EQUIPMENT

- Clean all equipment immediately after use with Water Soluble Brush Cleaner.

SPECIAL NOTES

- Before priming any areas showing black or green mould growth must be treated with Biocidal Wash.

DATA SHEET

407

BONDING PRIMER (PREVIOUSLY “P1” PRIMER)

(Page 2 of 3)

V1-28/11/2014

STORAGE AND HANDLING

- The product contains solvents and is highly flammable.
 - Sealed, unused containers should be stored in a cool environment, preferably below 25°C.
 - Refer to the 16 point Safety Data Sheet.
-

DATA SHEET

407
BONDING PRIMER (PREVIOUSLY "P1" PRIMER)

(Page 3 of 3)

V1-28/11/2014

TECHNICAL DATA

| | |
|-----------------------------|---------------------------|
| COLOUR | : Clear |
| DENSITY @ 25°C | : 1.02 gm/cm ² |
| CONSISTENCY | : Thin Liquid |
| VISCOSITY @ 25°C | : < 500cps |
| SOLID CONTENT | : 50% |
| FLASH POINT | : 32°C |
| TOUCH DRY (50% RH) | : 30-60 mins. |
| HARD DRY | : 24Hrs @ 25°C |
| THINNERS | : Xylol |
| SHELF LIFE | : 12 months |
| PACKAGING | : 1 and 5 litres |

The technical data furnished is obtained from controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven fault our liability will be limited to the replacement of the product only. It is the users' responsibility to confirm the currency of product data sheets.