

**DATA SHEET**

**708**  
**FLOW AGENT**

(Page 1 of 2)

V1-28/11/2014

**DESCRIPTION**

- 708 Flow Agent is a colourless liquid.

**FEATURES**

- Economical.
- Easy to use.

**USES**

- Sprayed on to metal Trowels to Aid in applying and screeding Polyurethane Binder/ Quartz Mixtures.
- Can be used to remove Polyurethane Binder from equipment before it cures.

**SAFETY**

- 708 flow agent is flammable.
- No Smoking or naked flames.
- Ensure adequate ventilation.
- Refer to 16 point Material Safety Data Sheet.

## DATA SHEET

### 708 FLOW AGENT

(Page 2 of 2)

V1-28/11/2014

## TECHNICAL DATA

<b>MATERIAL TYPE</b>	: Solvent
<b>APPEARANCE</b>	: Water White
<b>SG</b>	: 0.860
<b>FLASH POINT</b>	: 30°C
<b>PACKAGING</b>	: 5L&20L
<b>STORAGE</b>	: Ideally between 5°C and 25°C
<b>SHELF LIFE</b>	: 12 months

The technical data furnished is obtained from controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven fault our liability will be limited to the replacement of the product only. It is the users' responsibility to confirm the currency of product data sheets.