

DATA SHEET

717 **SUPER RUST CONVERTER**

(Page 1 of 3)

V1-28/11/2014

DESCRIPTION

- A ready to use water based rust converter and protective coating in one product.

USES

- Where blast cleaning is impractical

PROPERTIES

- Converts iron oxide (rust) to ferrous tannate
- Colour changes to black when reaction is complete
- Easy to apply by brush, roller or spray
- Water based, VOC compliant and environmentally friendly.

PREPARATION AND APPLICATION

- All surfaces to be clean and sound and free of dust, oil and dirt
- Wire brush to remove loose rust
- Apply 1 or 2 coats by brush, roller or spray @ 10 – 12m²/litre per coat
- Clean all equipment with water

OVERCOATING

- Allow to dry for 3-4hrs then overcoat with water based or solvent based top coats.
- Different surfaces and environmental conditions require specific painting systems to produce the best possible results. It is therefore recommended that you contact a Sales Representative for advice on all your painting requirements, whenever possible.

DATA SHEET

717
SUPER RUST CONVERTER

(Page 2 of 3)

V1-28/11/2014

HEALTH AND SAFETY

- Wear suitable face masks when spraying. Wash up with soap and water. Refer to the 16 point Material Safety data Sheet.
-

HOW TO SPECIFY

- All Rusted surfaces to be suitable prepared and then coated with 512 Super Rust Converter according to the manufacturer's instructions

DATA SHEET

717

SUPER RUST CONVERTER

(Page 3 of 3)

V1-28/11/2014

TECHNICAL DATA

TYPE	: A tannate based rust converter				
COLOUR	: Milky yellow which changes to black				
DRYING TIME	Temperature	5°C	10°C	20C	30°C
	Surface Dry	2Hrs	1Hr	½Hr	½Hr
	Hard Dry	9Hrs	8Hrs	6Hrs	4Hrs
No. OF COATS	: 1 or 2				
RECOAT TIME	: 3 to 48hrs				
APPEARANCE	: Matt black when cured				
VOLUME SOLIDS	: 40%				
SPREAD RATE	: 10- 12m ² /litre				
APPLICATION TEMP.	: 5 to 45°C				
PACKAGING	: 0.5L , 1L, 5L, 25L				
CLEANING	: Water				

The technical data furnished is obtained from controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven fault our liability will be limited to the replacement of the product only. It is the users' responsibility to confirm the currency of product data sheets.